



## TECHNICAL DATA SHEET

### 740 SHREDDER OIL

740 Shredder Oil is a specially formulated, highly refined, good quality antiwear hydraulic oil exhibiting good oxidation resistance, rust and corrosion protection and foam resistance.

740 Shredder Oil meets or exceeds the following specifications: Dennison HF-2, Vickers I-286-S, Cincinnati Milacron P-68, P-69, P-70.

### TYPICAL PROPERTIES

#### PROPERTY

Gravity, API (D287)	31.8
Viscosity, cSt/40°C (D445)	22.0
Viscosity, cSt/100°C (D445)	4.4
Viscosity Index (D2270)	100
Demulsibility, 54.5°C, Min	20
Oxidation Stability, TOST (D943)	3000+
Color (D1500)	0.5
FZG Pass, Load Stage	10
Zinc % wt	0.03
Cu Corrosion, 3 Hrs @ 100°C	1A
Rust (D665)	Pass
Flash Point, COC °F (D92)	405
Pour Point °C (D97)	0

Dahle North America, Inc.  
49 Vose Farm Road  
Peterborough, NH 03458

Tel: (603) 924-0003 • Fax: (603) 924-1616 • [info@dahle.com](mailto:info@dahle.com)

[www.dahle.com](http://www.dahle.com)